



Nereus

Penetrating Lubricating Oil

Biobased

Nereus is a high performance penetrant and lubricating oil for general purpose use. Formulated with the best optimised natural seed oils and select additives, it surpasses the lubricity and performance of conventional lubricants

Biobased

Biobased, biodegradable, non-bioaccumulative, non-aquatic toxic and not toxic to plants. Based on evaluation of the base oils and the finished products, the biobased products are designed to be biodegradable, aquatically non-toxic, not bioaccumulative and with no impact on plants as determined by known test methods. Nevertheless, the use of all the products are subject to the local ordinances and ultimate responsibility for impact remains with the users

Applications

- Multipurpose lubricant and penetrant
- Loosens rusty bolts
- Quiets squeaky hinges and moving parts
- Deters water
- Protects from rust and corrosion
- Protects purpose cutting, grinding and drilling metals
- Milling, tapping and reaming

Benefits

- Made from plant oils, better for your health
- Multiple application- reduces product inventory
- Superior lubricity improves productivity
- Cooler operating and less smoke allow higher operating speeds
- Safe for all metals
- Will help your business comply with ISO-14000
- Does not contain chlorine
- High flash and fire points
- Made from renewable crop based vegetable oils - reduces foreign oil dependence

Properties	Test Method	Typical Values
Appearance	Visual	Light yellow
Viscosity@ 40°C, cSt	ASTM D 445	40
Viscosity@ 100°C, cSt	ASTM D 445	8.5
Flash Point °C, °F	ASTM D 92	310(590)
Fire Point °C, °F	ASTM D 92	3148(658)
4-Ball Wear, mm	ASTM D 4172	0.47
4-Ball Weld, kg	ASTM D 2596	250
Pin & Vee Block Test	ASTM D 3233A	3335 lbs
Pour Point, °C, °F	ASTM D 97	-20 (-4)
Rust Prevention (Distilled)	ASTM D 665 A	Pass, None
Rust Prevention (Syn. Seawater)	ASTM D 665 B	Pass, None
Base Oil Aquatic Toxicity	Daphnia	Non- Toxic
Base Oil Biodegradability	OECD	Pass

Packaging	Gallons	Litres
Pail	5	19
Drum	55	208
Bulk Tote	As required	1040

DATA PROVIDED IN THIS BULLETIN IS TO BE CONSIDERED AS REPRESENTATIVE OF CURRENT PRODUCTION GENERALLY AND NOT AS SPECIFICATIONS. WHILE ALL THE DATA PRESENTED IN THIS BULLETIN IS BELIEVED TO BE RELIABLE AND BECAUSE CONDITIONS OF USE ARE BEYOND OUR CONTROL, LUBITEC MAKES NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR AS TO THE THE CORRECTNESS OR SUFFICIENCY OF DATA HEREIN PRESENTED. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE FITNESS OF ANY PRODUCT FOR ITS INTENDED PURPOSE. NO AGENT, REPRESENTATIVE OR EMPLOYEE OF THIS COMPANY IS AUTHORISED TO VARY ANY OF THE TERMS OF THIS NOTICE. TO CONTINUE TO PROVIDE SUPERIOR QUALITY, LUBITEC RESERVES THE RIGHT TO CHANGE THE COMPOSITION OF ITS PRODUCTS WITHOUT NOTICE.

